Lenovo ThinkVision E1922 Specifications

Product Specifications Reference (PSREF)

Name	**E1922 Wide Flat Panel Monitor**
Case color	**Business black**
Type-model	**60B8AAR6US**
Panel	TFT-LCD, twisted nematic (TN), White LED backlight
Viewable image size	**18.5"** (**470mm**) diagonal
Max view area (W x H)	16.1" x 9.1" / 409.8mm x 230.4mm
Native resolution	**1366x768**
Aspect ratio	16:9
Pixel pitch (mm)	.300mm
Dot/Pixel per Inch	85 dpi
Brightness	250 nits or cd/m² (typical)
Contrast ratio	1000:1 (typical)
Pixel response time	5ms (typical)
Color gamut	72%
Viewing angle at 10:1 CR	170° (+/- 85°) horizontal, 160° (+/- 80°) vertical
Stand	Tilt adjustable stand
Bezel width	*Sides:* 0.73" (18.5mm)
Dimensions (HxWxD)	13.44" H x 17.65" W x 6.58" D; 341.5mm H x 448.4mm W x 167.2mm D
Power supply	13.7 watts typical, 17 watts maximum, <0.5 watts standby/suspend, universal, integrated (no external brick-like power supply)
Weight	6.03 lb; 2.74 kg
Limited warranty[4]	**3 year** (includes backlight)
Available date	March 2014

Features

- Widescreen 18.5-inch monitor
- Supports HD 1366x768 resolution
- Supports VESA mount (100mm)
- Mercury free panel and arsenic free glass
- Kensington lock slot ready for enhanced security
- Support Lenovo Tiny PC via VESA mount
- Microsoft® Windows® 7 certified
- Microsoft Windows 8 / Windows 8.1 certified

ThinkVision E1922 Wide Monitor

VESA-compliant[2]	VESA DPMS-compliant
Power management	ENERGY STAR® 6.0
Ergonomics	ISO 9241-307
Emission standards	FCC Class B
Environmental	TCO (TCO Displays 6.0), WEEE, RoHS, **EPEAT™ Gold rating**

Preset resolutions	VGA: 640x350, 640x480, 720x400 SVGA: 800x600, 832x624 XGA: 1024x768, 1152x864 SXGA: 1280x1024 WXGA: 1366x768
Presets / user settings	Standard presets: 15 user settings: 16

Viewing adjustments	*Tilt:* 20° backward, -5° forward
Rotating screen	None
On screen display	On screen display with digital user controls (8 languages)
Control features	Direct access (control buttons on front) for automatic image setup and adjustment for brightness
Multiple input	None
Monitor connectors	VGA 15-pin D-shell, analog, blue
Signal cables	detachable, VGA 15-pin D-shell at each end, analog, 1.8 meter
Mounting features	Wall or desk mounting using the Extend Arm or third-party accessories meeting the VESA FPMPMI® (100mm mount)
Security	Security keyhole for attachment of optional cable lock (Kensington® lock-compatible)

Ship group	Monitor with stand, 1.8 meter analog signal cable, 1.8 meter black power cord

Limited Warranty

See details at **http://support.lenovo.com/en_US/guides-and-manuals/detail.page?DocID=UM008281**

Accessories

Kensington MicroSaver Cable Lock	73P2582
Kensington Twin Head Cable Lock	45K1620

See details at **www.lenovo.com/support/monitoraccessories**

See all monitors at **www.lenovo.com/thinkvision**

See footnotes for important warranty information
US model announced February 18, 2014

© Lenovo